

MOUSSOL®-APS Premium 3/6 F-15 #3971

ALCOHOL RESISTANT AFFF FOAM CONCENTRATE



Description

MOUSSOL®-APS Premium 3/6 F-15 is a pseudo-plastic, alcohol resistant AFFF fire extinguishing foam concentrate. Polymer film formers, aqueous film forming fluorine components and foam stabilisers characterise the composition of this excellent fire extinguishing foam concentrate. In parts, the product is made from natural, renewable sources. Using only the latest C6 technology, the fluorinated components contained in MOUSSOL®-APS Premium 3/6 F-15 are in full compliance with Directive EU 757/2010.

Properties

MOUSSOL®-APS Premium 3/6 F-15 has excellent fire performance, flowability and burn-back resistance on both polar and non-polar, foam destroying liquids. The polymer film has a specific, foam stabilising effect. It is formed by a physical interaction between a polar solvent and the foam layer above. On non-polar hydrocarbons, an extremely thin aqueous film is formed which flows ahead of the foam. A relatively short water drainage time enhances aqueous film formation and the flowability of the foam. This effect reduces control times significantly and cools down the fire source.

MOUSSOL®-APS Premium 3/6 F-15 provides for a swift and effective fire fighting success with excellent performance reserves. The risk of re-ignition of extinguished areas is reduced significantly.

Application

MOUSSOL®-APS Premium 3/6 F-15 is used with all standard low and medium expansion foam installations and mobile equipment. It is specially designed for polar, foam destroying liquids, e.g. alcohols, esters, ketones as well as non-polar hydrocarbons, e.g. petroleum products. The induction rate is 5-6% in water for polar solvents and 3% for hydrocarbon fires. For medium expansion foam applications on hydrocarbon fires the induction rate is 3-6%. Aqueous film forming fluorine components allow for non-aspirated application on non-polar hydrocarbons.

MOUSSOL®-APS Premium 3/6 F-15 is also used to cover spilled chemicals to prevent flammable and toxic gas emissions. A gentle foam application is required in order to combat polar solvent fires effectively (see technical leaflet TM 037 „Extinguishing alcohol fires“). Pump-supported induction may be required for temperatures below 5°C.

MOUSSOL®-APS Premium 3/6 F-15 is used with tap

water, seawater, brackish water and treated industrial water. When used in near electrical installations observe DIN/VDE-0132, or equivalent national standards.

Environment

None of the raw materials used in our products are banned. Our foam concentrates comply with the latest environmental regulations, such as 'Commission Regulation (EU) No 757/2010', amending '(EC) No 850/2004.' MOUSSOL®-APS Premium 3/6 F-15 will also comply with the 'significant new use rule (SNUR)' for long-chain perfluoroalkyl carboxylate proposed by the Environmental Protection Agency, which will come into effect in due course.

Compatibility with other foam concentrates

Mixing for immediate use:

MOUSSOL®-APS Premium 3/6 F-15 can be mixed at any proportion with equivalent foam concentrates if used immediately.

Mixing for long term storage:

It is not recommended to mix MOUSSOL®-APS Premium 3/6 F-15 with equivalent foam concentrates when stored. Prior to replenishment, the quality of MOUSSOL®-APS Premium 3/6 F-15 stocks should be examined by our laboratory.

Mixing with synthetic concentrates:

MOUSSOL®-APS Premium 3/6 F-15 must not be mixed with other types foam concentrates.

Mixing with other expanded foams:

MOUSSOL®-APS Premium 3/6 F-15 foam is compatible with all other generated fire fighting foams.

Compatibility with powder

MOUSSOL®-APS Premium 3/6 F-15 is suitable for the combined use with foam compatible dry chemical powders.

Packaging

MOUSSOL®-APS Premium 3/6 F-15 is available in plastic cans, plastic drums, IBC's (totes) and in bulk.

MOUSSOL®-APS Premium 3/6 F-15 #3971

ALCOHOL RESISTANT AFFF FOAM CONCENTRATE



Storage

MOUSSOL®-APS Premium 3/6 F-15 is stored long term in the sealed original containers or in non-corrosive plastic or stainless steel tanks. High temperatures up to 50°C do not affect the quality, neither does temporary freezing below the specified frost resistance limit (see technical leaflet TM 014 "Storage of synthetic foam concentrates"). Before re-filling foam concentrate stocks arrange for a quality check-up by our laboratory.

Shelf Life

MOUSSOL®-APS Premium 3/6 F-15 has a shelf life of >10 years, if stored according to our recommendations (see technical info leaflet TM014 'Storage of Synthetic Fire Extinguishing Foam Concentrates').

Conformity/Listings

MOUSSOL®-APS Premium 3/6 F-15 is approved as fire extinguishing agent for fires of class B according to the following standards:

DIN EN
1568

EN 1568:2008 - Certificate No.: KB-255/14
Part 3 (Heptane): IA/IA
Part 4 (Aceton): IA/IA --- (IPA): IA/IA
Part 1: Medium ex. --- Part 2: High ex.

LAST
fire

LASTfire
good --- good --- good

Physical properties and technical data		MOUSSOL®-APS Premium 3/6 F-15	
Recommended induction rate	3%	low expansion foam	non-polar liquids
	3-6%	medium expansion foam	non-polar liquids
	5-6%	low expansion foam	polar liquids
Foam expansion* (according to EN 1568)	5 - 9	low expansion foam*	
	20 - 40	medium expansion foam*	
	400 - 600	high expansion foam*	
25%/50% water drainage time* (according to EN 1568)	4 - 8 minutes	8 - 12 minutes	low expansion foam*
	1 - 4 minutes	4 - 8 minutes	medium expansion foam*
	2 - 5 minutes	4 - 6 minutes	high expansion foam*
Colour	colorless to yellow		
pH value	at 20°C	6,5 - 8,5	
Density	at 20°C	1,040 ± 0,02 g/ml	
Sediments	none		
Surface tension/Spreading coefficient	< 17,5 mN/m	> 3 mN/m (Cyclohexane)	
Frost resistance	-15°C		
Viscosity	at 20°C	< 250(100) mPa*s bei 75(375) 1/s	
	at 0°C	< 400(150) mPa*s bei 75(375) 1/s	
	at -15°C	< 500(200) mPa*s bei 75(375) 1/s	
Environmental acceptability	MOUSSOL®-APS Premium 3/6 F-15 is readily bio degradable. Fluorine components are not fully degradable. See material safety data sheet for further information.		
Special notes	MOUSSOL®-APS Premium 3/6 F-15 poses no health risk, provided it is used as intended as fire extinguishing foam. Firefighting exercise and testing may have to be agreed with local authorities. Consider when spraying persons with foam that they will not be able to breathe whilst covered with foam. See material safety data sheet for further information.		



Dr. STHAMER HAMBURG

Hauptsitz Hamburg:
Liebigstraße 5 • 22113 Hamburg/Germany
Tel.: +49 (0)40 736168-0 • Fax: +49 (0)40 736168-0

info@sthamer.com • www.sthamer.com

Verkaufsbüro Hannover:
Tel.: +49 (0)511 76835845
Fax: +49 (0)511 76835846

Verkaufsbüro Jena:
Tel.: +49 (0)3641 6353857
Fax: +49 (0)3641 6353859

